

FICHA TÉCNICA

WELDWELL®
KOBE
LASMAQUINASDESOLDAR



● TRABAJO
LIVIANO

● TRABAJO
SEMI-PESADO

● TRABAJO
PESADO

WELDWELL®



WELDWELL®
PC-150 KOBE

POWER SUPPLY	220V ± 15%
FREQUENCY	50 - 60HZ
PHASE	3PH
RATED INPUT (KVA)	26
OPEN CIRCUIT VOLTAGE(V)	330
AMPERAGE RANGE(A)	40-150
RATED DUTY CYCLE (31C°)	80%
RATED WORKING VOLTAGE(V)	96-140
EFFICIENCY	0.85
POWER FACTOR	0.93
MAX CUTTING THICKNESS (MM)	45
QUALITY CUTTING THICKNESS(MM)	30
COMPRESSED AIR PRESSURE (PSI)	40 - 80
POST FLOW TIME(KG)	0 - 5
DIMENSIÓN (L X W X H)(CM)	65*36*53
NET WEIGHT (KGS)	49



ENTRADA



3 FASE



60 Hz



● ACCESORIOS
INCLUIDOS



Guantes
de soldar.



Tierra con
cable.



Antorcha
PLASMA



Filtro de aire

● ACCESORIOS
QUE NO
INCLUYEN



Compresor
de aire



Mascara
de cortar

